

View Online at <https://aerobasegroup.com/nsn/4810-00-287-3929>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

850.0 degrees fahrenheit single response

Valve Operation Method:

Hydraulic

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Valve Size:

2.000 inches

Power Drive Operating Pressure:

600.0 pounds per square inch

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

6.500 inches 1st end

Face To Face Distance:

11.500 inches

Thickness:

1.000 inches 1st end

Bolt Hole Diameter:

0.688 inches 1st end

Bolt Circle Diameter:

5.000 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

3.625 inches 1st end

Special Features:

Flow control device and seat: steel, molybdenum; 2 end connections; second end relationship w/ first end: identical

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0