NSN 4810-00-289-1206



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-00-289-1206 Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **Current Rating In Amps:** 0.109 **Valve Operation Method:** Solenoid or manual Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Horizontal Valve Size: 1.250 inches **Inlet/outlet Operating Pressure Differential:** 150.0 pounds per square inch **Maximum Operating Pressure:** 250.0 pounds per square inch single response **Voltage In Volts And Current Type:** 110.0 ac **Outside Diameter:** 4.500 inches all ends **Face To Face Distance:** 5.750 inches Thickness: 0.406 inches all ends **Bolt Hole Diameter:** 0.562 inches all ends

Bolt Circle Diameter: 3.375 inches all ends Flange Face Design: Plain all ends Phase:

Single

Special Features:

Piston flow control w/pilot valve operating device

NSN 4810-00-289-1206

Solenoid Valve - Page 2 of 2



rrequency in Hertz:
60.0
Material:
Copper alloy
Media For Which Designed:
Air 1st response
Style Designator:
Straight through flanged ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0