NSN 4810-00-289-1206

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-289-1206

Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Current Rating In Amps:
0.109
Valve Operation Method:
Solenoid or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
1.250 inches
Inlet/outlet Operating Pressure Differential:
150.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Voltage In Volts And Current Type:
110.0 ac
Outside Diameter:
4.500 inches all ends
Face To Face Distance:
5.750 inches
Thickness:
0.406 inches all ends
Bolt Hole Diameter:
0.562 inches all ends
Bolt Circle Diameter:
3.375 inches all ends
Flange Face Design:
Plain all ends
Phase:
Single
Special Features:
Piston flow control w/pilot valve operating device

NSN 4810-00-289-1206 Solenoid Valve - Page 2 of 2

Frequency In Hertz:
60.0
Material:
Copper alloy
Media For Which Designed:
Air 1st response
Style Designator:
Straight through flanged ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0

