

View Online at <https://aerobasegroup.com/nsn/4810-00-294-2083>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Piston

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

195.0 degrees celsius single response

**Connection Style:**

Plain, optional en (pipe) all ends

**Current Rating In Amps:**

28.000

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal pipe all ends

**Mounting Position:**

Horizontal

**Power Drive Operating Pressure:**

5.0 pounds per square inch

**Inlet/outlet Operating Pressure Differential:**

145.0 pounds per square inch

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Thread Size:**

0.375 inches all ends

**Voltage In Volts And Current Type:**

110.0 ac and 28.0 dc

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Rubber flow control device

**Media For Which Designed:**

Air single response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Npt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0