NSN 4810-00-294-2083

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-294-2083

Thread Direction:

Right-hand all ends

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

195.0 degrees celsius single response

Connection Style:

Plain, optional en (pipe) all ends

Current Rating In Amps:

28.000

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal

Power Drive Operating Pressure:

5.0 pounds per square inch

Inlet/outlet Operating Pressure Differential:

145.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

0.375 inches all ends

Voltage In Volts And Current Type:

110.0 ac and 28.0 dc

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Material:

Rubber flow control device

Media For Which Designed:

Air single response

Style Designator:

Straight thru

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

NSN 4810-00-294-2083

Solenoid Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

