

View Online at <https://aerobasegroup.com/nsn/4810-00-304-4291>

Thread Direction:

Right-hand all ends

Aperture Diameter:

0.500 inches

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

240.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Current Rating In Amps:

0.100 and 0.091

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Power Drive Operating Pressure:

1.0 pounds per square inch

Inlet/outlet Operating Pressure Differential:

149.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

0.500 inches all ends

Voltage In Volts And Current Type:

110.0 ac and 120.0 ac and 110.0 dc and 120.0 dc

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Material:

Plastic flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0