NSN 4810-00-307-8384

Solenoid Valve - Page 1 of 2

1 washer and 2 bushing



View Online at https://aerobasegroup.com/nsn/4810-00-307-8384

Pipe Size Accommodated:
1.250 inches all ends
Aperture Diameter:
0.663 inches
Flow Control Device:
Disk
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Pressed-in
Connection Style:
Socket with brazing ring all ends
Valve Operation Method:
Solenoid
Connection Type:
Unthreaded internal pipe all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
5.0 pounds per square inch single response
Voltage In Volts And Current Type:
115.0 ac
Phase:
Single
Special Features:
Valve size 1.250in
Frequency In Hertz:
60.0
Material:
Stainless steel flow control device and rubber butadiene-acrylonitrile class nbr flow control device
Material Specification:
Astm b140 assn standard single material response seat
Media For Which Designed:
Water, fresh single response
Surface Treatment:
Zinc
Surface Treatment Specification:
Qq-z-325, type 3 federal specification single treatment response
Style Designator:
Straight thru
Furnished Items And Quantity:

NSN 4810-00-307-8384

Solenoid Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0