NSN 4810-00-311-5329

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-311-5329

| Thread Direction: |
|--|
| Right-hand all ends |
| Flow Control Device: |
| Piston |
| Flow Control Device Normal Operation Position: |
| Open |
| Maximum Operating Temp: |
| 130.0 degrees fahrenheit single response |
| Connection Style: |
| Plain, optional en (pipe) all ends |
| Current Rating In Amps: |
| 0.400 |
| Valve Operation Method: |
| Solenoid |
| Connection Type: |
| Threaded internal pipe all ends |
| Mounting Position: |
| Horizontal |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch 2nd response |
| Thread Size: |
| 0.750 inches all ends |
| Voltage In Volts And Current Type: |
| 60.0 ac |
| Phase: |
| Single |
| Special Features: |
| Valve size 0.750 |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Stainless steel flow control device |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Npt all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4810-00-311-5329

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0