NSN 4810-00-339-2373

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-339-2373

Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
1.125 inches
Flow Control Device:
Needle
Flow Control Device Normal Operation Position:
Closed
Bolt Hole Quantity:
5 2nd end
Connection Style:
Plain (tube) 1st end
Width:
1.438 inches 2nd end
Length:
1.359 inches 2nd end
Current Rating In Amps:
0.590
Valve Operation Method:
Solenoid
Flange Shape:
Triangular with holes 2nd end
Connection Type:
Threaded external tube 1st end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
40.0 pounds per square inch single response
Thread Size:
0.625 inches 1st end
Voltage In Volts And Current Type:
30.0 dc
Thickness:
0.078 inches 2nd end
Bolt Hole Diameter:
0.156 inches 2nd end
Bolt Circle Diameter:
1.125 inches 2nd end
Flange Face Design:
Plain 2nd end

NSN 4810-00-339-2373

Solenoid Valve - Page 2 of 2

Material:

Stainless steel flow control device

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Cadmium

Style Designator:

Angle

Thread Series Designator:

Unef 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

