NSN 4810-00-347-6632

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-347-6632

Thread Direction:
Right-hand all ends
Aperture Diameter:
0.750 inches
Flow Control Device:
Diaphragm
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
240.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Current Rating In Amps:
0.174
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal or vertical
Inlet/outlet Operating Pressure Differential:
150.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Voltage In Volts And Current Type:
110.0 ac and 120.0 ac
Phase:
Тwo
Frequency In Hertz:
50.0 and 60.0
Material:
Plastic polytetrafluoroethylene flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Straight thru
Thread Series Designator:
Npt all ends
Shelf Life:
N/a

NSN 4810-00-347-6632

Solenoid Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

