## NSN 4810-00-351-6839

Flow Control Device Normal Operation Position:

Solenoid Valve - Page 1 of 2

Flow Control Device:

Piston

Closed



View Online at https://aerobasegroup.com/nsn/4810-00-351-6839

| Bolt Hole Quantity:  |
|--|
| 4 1st end  |
| Maximum Operating Temp:                                    |
| 160.0 degrees fahrenheit single response                   |
| Width:   |
| 2.750 inches 1st end                                       |
| Length:  |
| 3.000 inches 1st end                                       |
| Current Rating In Amps:                                    |
| 1.000  |
| Valve Operation Method:                                    |
| Solenoid   |
| Flange Shape:  |
| Rectangular with holes 1st end                             |
| Connection Type:   |
| Flange 1st end   |
| Mounting Position:   |
| Horizontal   |
| Valve Size:  |
| 3.000 inches   |
| Maximum Operating Pressure:                                |
| 60.0 pounds per square inch single response                |
| Voltage In Volts And Current Type:                         |
| 18.0 dc and 30.0 dc  |
| Face To Face Distance:                                     |
| 6.090 inches   |
| Thickness:   |
| 0.250 inches 1st end                                       |
| Bolt Hole Diameter:  |
| 0.328 inches 1st end                                       |
| Bolt Circle Diameter:                                      |
| 2.124 inches 1st end                                       |
| Center To Center Distance Between Bolt Holes Along Length: |
| 2.375 inches 1st end                                       |
| Center To Center Distance Between Bolt Holes Along Width:  |
| 2.375 inches 1st end                                       |
| Flange Face Design:  |
| Plain 1st end  |
|  |

## **NSN 4810-00-351-6839** Solenoid Valve - Page 2 of 2



| Material:   |
|---|
| Stainless steel                                   |
| Media For Which Designed:                         |
| Fuel/oil, hydrocarbon single response             |
| Surface Treatment:                                |
| Anodize   |
| Style Designator:                                 |
| Straight through flanged ends                     |
| Reference Number Differentiating Characteristics: |
| As differentiated by source controldwg number     |
| Shelf Life:                                       |
| N/a   |
| Unit Of Measure:                                  |
|   |
| Demilitarization:                                 |
| Yes - demil/mli                                   |

Fiig: A046b0