NSN 4810-00-375-9974



Solehold valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4810-00-375-9974
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.062 inches
Flow Control Device:
Poppet
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
0.174
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe 2nd end
Mounting Position:
Horizontal
Inlet/outlet Operating Pressure Differential:
100.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Voltage In Volts And Current Type:
115.0 ac
Phase:
Single
Special Features:
W/explosion proof solenoid
Frequency In Hertz:
50.0 and 60.0
Material:
Stainless steel
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:

Straight thru

Thread Series Designator:

Npt 1st end

NSN 4810-00-375-9974

Solenoid Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0