## NSN 4810-00-375-9974

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-375-9974

## Thread Direction: Right-hand 1st end Aperture Diameter: 0.062 inches

### Flow Control Device:

Poppet

#### Flow Control Device Normal Operation Position:

Closed

#### Maximum Operating Temp:

180.0 degrees fahrenheit single response

#### Connection Style:

Plain, optional en (pipe) 1st end

#### **Current Rating In Amps:**

0.174

#### Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal pipe 2nd end

#### Mounting Position:

Horizontal

#### Inlet/outlet Operating Pressure Differential:

100.0 pounds per square inch

#### Maximum Operating Pressure:

150.0 pounds per square inch single response

**Thread Size:** 

0.250 inches 1st end

#### Voltage In Volts And Current Type:

115.0 ac

Phase:

Single

#### **Special Features:**

W/explosion proof solenoid

#### Frequency In Hertz:

50.0 and 60.0

Material:

Stainless steel

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Straight thru

#### **Thread Series Designator:**

Npt 1st end

# NSN 4810-00-375-9974

Solenoid Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

