NSN 4810-00-418-3049

Butterfly Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-418-3049
Maximum Operating Temp:
400.0 degrees fahrenheit single response
End Application:
Applicable t.O. 9p5-5-98-3 fig 4; u/o code c; overhaul parts kit p/n f61c2480
Current Rating In Amps:
1.000
Valve Operation Method:
Solenoid
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Maximum Operating Pressure:
50.0 pounds per square inch single response
Voltage In Volts And Current Type:
20.0 dc and 29.0 dc
Opening Pressure Setting:
20.0 pounds per square inch
Outside Diameter:
3.250 inches all ends
Face To Face Distance:
3.940 inches
Thickness:
0.188 inches all ends
Flange Face Design:
Plain all ends
Butterfly Valve Size:
3.000 inches
Special Features:
Manufacturers suggested name is three inch pneumatic solenoid shutoff valve; service fluid air; weight 4.0 lbs
Material:
Aluminum alloy body
Media For Which Designed:
Air single response
Style Designator:
Straight through flanged ends
Furnished Items And Quantity:
1 filter

N/a

Shelf Life:

NSN 4810-00-418-3049

Butterfly Valve - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0