

View Online at <https://aerobasegroup.com/nsn/4810-00-432-9554>

**Thread Direction:**

Right-hand

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Threaded

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**Connection Style:**

Plain, optional en (pipe) 1st end

**Current Rating In Amps:**

0.054

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal pipe 1st end

**Thready Qty Per Inch (tpi):**

14 all ends

**Maximum Operating Pressure:**

250.0 pounds per square inch single response

**Thread Size:**

0.500 inches all ends

**Voltage In Volts And Current Type:**

120.0 ac

**Center To Center Distance:**

2.000 inches

**Phase:**

Single

**Special Features:**

Watertight and explosion proof, solenoid enclosure

**Frequency In Hertz:**

60.0

**Material:**

Rubber flow control device

**Material Specification:**

Rubber, buna-n assn standard single material response flow control device

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Tee w/offset

**Thread Series Designator:**

Npt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0