NSN 4810-00-435-1070

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-435-1070 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.172 inches Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** Flared (tube) 1st end **Current Rating In Amps:** 0.660 **Valve Operation Method:** Solenoid **Connection Type:** Threaded external tube 1st end **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 120.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Voltage In Volts And Current Type:** 18.0 dc and 30.0 dc **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material: Stainless steel seat Media For Which Designed: Air single response **Surface Treatment: Passivate Style Designator: Thread Series Designator:**

Straight thru Unf 1st end Shelf Life: N/a

NSN 4810-00-435-1070 Solenoid Valve - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

Demilitarization:

No

Fiig:

A046b0