# NSN 4810-00-435-5661

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-435-5661

# Thread Direction:

Right-hand 3rd end

**Flow Control Device:** 

Disk

# Flow Control Device Normal Operation Position:

Closed

#### **Connection Style:**

Plain, optional en (pipe) 3rd end

# **Current Rating In Amps:**

0.083

#### Valve Operation Method:

Solenoid

#### Connection Type:

Unthreaded internal tube 1st end

#### **Mounting Position:**

Horizontal or vertical

#### Maximum Operating Pressure:

50.0 pounds per square inch single response

#### Thread Size:

0.250 inches 3rd end

# Voltage In Volts And Current Type:

120.0 ac

#### **Outside Diameter Tube Accommodated:**

0.250 inches 1st end

Phase:

Single

#### Frequency In Hertz:

60.0

#### Material:

Stainless steel body

#### Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Cross

#### **Thread Series Designator:**

Npt all ends

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# **NSN 4810-00-435-5661** Solenoid Valve - Page 2 of 2

Fiig: A046b0

