NSN 4810-00-436-8236

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-436-8236

| Pipe Size Accommodated: |
|--|
| 1.250 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Flow Control Device Normal Operation Position: |
| Open |
| Connection Style: |
| Plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Solenoid |
| Connection Type: |
| Unthreaded internal tube 2nd end |
| Mounting Position: |
| Horizontal |
| Thready Qty Per Inch (tpi): |
| 11-1/2 1st end |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 1.250 inches 1st end |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Outside Diameter Tube Accommodated: |
| 1.625 inches 2nd end |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Stainless steel flow control device |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Nptf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4810-00-436-8236 Solenoid Valve - Page 2 of 2



Fiig:

A046b0