NSN 4810-00-438-3960

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-438-3960

| Offset Distance: |
|--|
| 0.625 inches |
| Flow Control Device: |
| Poppet |
| Flow Control Device Normal Operation Position: |
| Closed |
| Bolt Hole Quantity: |
| 4 all ends |
| Maximum Operating Temp: |
| 65.0 degrees fahrenheit single response |
| Width: |
| 1.594 inches all ends |
| Length: |
| 1.594 inches all ends |
| Valve Operation Method: |
| Solenoid |
| Flange Shape: |
| Rectangular with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal |
| Maximum Operating Pressure: |
| 30.0 pounds per square inch single response |
| Voltage In Volts And Current Type: |
| 18.0 dc and 30.0 dc |
| Face To Face Distance: |
| 5.392 inches |
| Thickness: |
| 0.2655 inches 1st end |
| Bolt Hole Diameter: |
| 0.190 inches all ends |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.156 inches all ends |
| Center To Center Distance Between Bolt Holes Along Width: |
| 1.156 inches all ends |
| Flange Face Design: |
| Plain 1st end |
| Special Features: |
| 2 ea, 10-32 diameter bolt holes on inlet flange not drilled thru |
| Material: |
| Aluminum alloy seat |

NSN 4810-00-438-3960

Solenoid Valve - Page 2 of 2



| Media For Which Designed: |
|--|
| Fuel/oil, hydrocarbon single response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Straight through w/offset flanged ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A046b0