NSN 4810-00-449-0507

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-449-0507 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.500 inches Flow Control Device: Diaphragm Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** 100.0 pounds per square inch **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Phase: Single Frequency In Hertz: 50.0 and 60.0 Material: Rubber butadiene-acrylonitrile class nbr seat Media For Which Designed: Air 1st response **Style Designator:** Straight thru **Thread Series Designator:** Npt all ends Shelf Life: N/a

Unit Of Measure:

NSN 4810-00-449-0507

Solenoid Valve - Page 2 of 2



| _ | | | | | | |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | tor | 172 | + 1 | nn | |
| | | | | | | |

No

Fiig:

A046b0