## NSN 4810-00-465-1523

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-465-1523 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Current Rating In Amps:** 0.140 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Vertical **Maximum Operating Pressure:** 350.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Voltage In Volts And Current Type:** 110.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Water-oil-gas single response **Style Designator:** Straight thru **Thread Series Designator:** Npt all ends **Reference Number Differentiating Characteristics:** 110 v ac. 300 psi for water 3/4 in. Orifice 3/4 in. Nom pipe size Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4810-00-465-1523

Solenoid Valve - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A046b0