

View Online at <https://aerobasegroup.com/nsn/4810-00-481-3642>

Thread Direction:

Right-hand all ends

Aperture Diameter:

Between 0.094 inches and 0.125 inches

Flow Control Device:

Plug

Flow Control Device Normal Operation Position:

Closed

Renewable Seat Ring Type:

Bonded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Current Rating In Amps:

0.080 and 0.090

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal

Inlet/outlet Operating Pressure Differential:

200.0 pounds per square inch

Maximum Operating Pressure:

50.0 pounds per square inch single response

Thread Size:

0.250 inches all ends

Voltage In Volts And Current Type:

110.0 ac and 120.0 ac

Phase:

Single

Special Features:

Explosion proof construction

Frequency In Hertz:

50.0 and 60.0

Material:

Stainless steel flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Straight thru

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0