

View Online at <https://aerobasegroup.com/nsn/4810-00-497-2375>

**Thread Class:**

3b

**End Connection Quantity:**

4

**Valve Discharge Flow Rate:**

2.1 gallons per minute

**End Application:**

T.O. 9h8-14-267-3 fig 4-1; u/o code e

**Current Rating In Amps:**

1.5

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal boss

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

0.438 inches

**Body Material:**

Aluminum alloy

**Maximum Operating Temperature And Media For Which Designed:**

275.0 degrees fahrenheit propane

**Voltage In Volts And Current Type:**

18.0 dc and 30.0 dc

**Flow Pattern Quantity:**

4

**Spool Position Quantity:**

3

**Spool Quantity:**

1

**Special Features:**

Manufacturers suggested name valve - hydraulic solenoid selector; fluid hydraulic fluid mil-h-5606 or mil-h-46170; fluid temp range -65 to +275 degrees feh; ambient temp range -65 to +275 degrees feh; cyl port pressures: operating 300 to 3000 psig, proof 4500 psig, burst 7500 psig; return port pressures: operating 1000 psig, proof 1500 psig, burst 7500 psig; rated flow 1.2 gpm at 30 psi maximum pressure drop from pressure port to cyl or cyl to return port; dry wt 0.90 lbs; this is a four way, 3 position valve with two solenoids; major component parts spool & sleeve assembly 2632829, spool 2632830, body 2632505; this valve has an improved potting compound per mil-s-23586a

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**