## NSN 4810-00-507-0326

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-507-0326

Flow Control Books
Flow Control Device:
Disk  Remot Type:
Bonnet Type:
Inside spring  Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Valve Operation Method:
Hydraulic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
7.690 inches all ends
Face To Face Distance:
15.000 inches
Thickness:
1.000 inches all ends
Bolt Hole Diameter:
0.690 inches all ends
Bolt Circle Diameter:
6.560 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Operation pressure connection 0.375 in. Union nut
Material:
Nickel alloy r-405 stem
Material Specification:
Qq-n-281 cl b cd federal specification single material response stem
Media For Which Designed:
Water, salt single response
Style Designator:
Straight through flanged ends
Specification Data:
81349-mil-v-17501 government specification

## NSN 4810-00-507-0326

Globe Valve - Page 2 of 2



Sne	cific	ation	Or	Stai	nda	rd.	
JUE	CHIC	auon	OI.	Otal	IIUa	II U.	

1 type and 2 class and 4in. Size

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-b-16541 spec.