## NSN 4810-00-513-4908

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-513-4908

## **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Poppet Flow Control Device Normal Operation Position: Open **Connection Style:** Plain, optional en (pipe) 1st end **Current Rating In Amps:** 0.500 Valve Operation Method: Solenoid **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 18 1st end Inlet/outlet Operating Pressure Differential: 40.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.562 inches 1st end Seat Angle: 60.0 degrees 1st end Voltage In Volts And Current Type: 18.0 dc and 30.0 dc **Outside Diameter Tube Accommodated:** 0.375 inches 1st end **Special Features:** 3 mtg holes 0.205 in. Id Material: Steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Angle **Test Data Document:** 00502-ht26610 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unf 1st end

## NSN 4810-00-513-4908

Solenoid Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

