

View Online at <https://aerobasegroup.com/nsn/4810-00-513-4908>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Open

Connection Style:

Plain, optional en (pipe) 1st end

Current Rating In Amps:

0.500

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Inlet/outlet Operating Pressure Differential:

40.0 pounds per square inch

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Seat Angle:

60.0 degrees 1st end

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Special Features:

3 mtg holes 0.205 in. Id

Material:

Steel seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Angle

Test Data Document:

00502-ht26610 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0