NSN 4810-00-516-3541



Solenoid Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4810-00-516-3541
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
Between 0.010 inches and 0.011 inches
Offset Distance:
0.680 inches
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Open
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Current Rating In Amps:
0.960
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
16 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Voltage In Volts And Current Type:
18.0 dc and 30.0 dc
Outside Diameter Tube Accommodated:
0.500 inches 1st end

Material:

Steel seat

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Style Designator:

Straight through w/offset

Thread Series Designator:

Unf 1st end

NSN 4810-00-516-3541

Solenoid Valve - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0