## NSN 4810-00-528-2555

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-528-2555 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.375 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open **Connection Style:** G4 gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 18 1st end **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end **Voltage In Volts And Current Type:** 18.0 dc and 30.0 dc Material: Aluminum alloy seat Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Style Designator:** Err-090 **Test Data Document:** 36659-695053 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unjf 1st end Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 4810-00-528-2555

Solenoid Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0