

View Online at <https://aerobasegroup.com/nsn/4810-00-528-2606>

**Body Material:**

Aluminum alloy

**Outside Surface Treatment:**

Anodized, mil-a-8625

**Body Style:**

Tee

**Stem Material:**

Any acceptable

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Flared

**First End Outside Diameter Tube Accommodated:**

0.375 inches

**First End Thread Size And Series/type Designator:**

9/16&18 unf

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Second End Relationship With First End:**

Not identical

**Second End Connection Type:**

Threaded internal boss

**Second End Style Designator:**

Gasket seal

**Second End Thread Size And Series/type Designator:**

9/16&18 unf

**Second End Thread Class:**

3b

**Second End Thread Direction:**

Right-hand

**Third End Relationship With Preceding Ends:**

Identical with second end

**Seat Material:**

Any acceptable

**First End Seat Angle In Deg:**

37.0

**Packing Material:**

Rubber, synthetic, mil-p-5516, class a

**Flow Control Device Material:**

Any acceptable

**End Connection Quantity:**

3

**Mounting Facility:**

Bolts

**Outlet Pressure Range:**

+1000.0 to 1500.0 pounds per square inch

**Regulation Type:**

Automatic single stage

**Valve Loading Method:**

Spring

**Maximum Inlet Pressure Rating:**

3000.0 pounds per square inch

**Outlet Pressure Accuracy Rating:**

Not rated

**Filter:**

Not included

**Temperature Rating:**

Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A21100