NSN 4810-00-528-2606

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-528-2606 **Body Material:** Aluminum alloy **Outside Surface Treatment:** Anodized, mil-a-8625 **Body Style:** Tee Stem Material: Any acceptable Media For Which Designed: Hydraulic fluid, phosphate-ester base **First End Connection Type:** Threaded external tube First End Style Designator: Flared First End Outside Diameter Tube Accommodated: 0.375 inches First End Thread Size And Series/type Designator: 9/16&18 unf First End Thread Class: За **First End Thread Direction:** Right-hand **Second End Relationship With First End:** Not identical **Second End Connection Type:** Threaded internal boss Second End Style Designator: Gasket seal Second End Thread Size And Series/type Designator: 9/16&18 unf **Second End Thread Class:** 3b **Second End Thread Direction:** Right-hand Third End Relationship With Preceding Ends: Identical with second end **Seat Material:** Any acceptable First End Seat Angle In Deg: 37.0 **Packing Material:**

Rubber, synthetic, mil-p-5516, class a

NSN 4810-00-528-2606

Fluid Pressure Regulating Valve - Page 2 of 2



Flow Control Device Material:
Any acceptable
End Connection Quantity:
3
Mounting Facility:
Bolts
Outlet Pressure Range:
+1000.0 to 1500.0 pounds per square inch
Regulation Type:
Automatic single stage
Valve Loading Method:
Spring
Maximum Inlet Pressure Rating:
3000.0 pounds per square inch
Outlet Pressure Accuracy Rating:
Not rated
Filter:
Not included
Tempurature Rating:
Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A21100