

View Online at <https://aerobasegroup.com/nsn/4810-00-528-3685>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Ball

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Plain, optional en (pipe) 1st end

Current Rating In Amps:

1.500

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Seat Angle:

60.0 degrees 1st end

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Special Features:

2 mtg holes 0.210 in. Dia, spaced 1.125 in. C to c

Material:

Stainless steel flow control device

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Test Data Document:

43999-na5-6331 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0