

View Online at <https://aerobasegroup.com/nsn/4810-00-529-3253>

Thread Class:

3b

End Connection Quantity:

4

Valve Discharge Flow Rate:

6.0 gallons per minute

End Application:

Applicalbe t.O. 9h8-14-110-4 fig 2-5

Current Rating In Amps:

0.7

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.750 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Flow Pattern Quantity:

4

Spool Position Quantity:

3

Spool Quantity:

2

Special Features:

Cmanufacturers suggested name valve assembly, 4 way, solenoid operated selector; media fluid per mil-h-5606; valve meets mil-v-791 (2)
; pressures: operating 3000 psig, proof 4500 psig, burst 7500 psig

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A506h0