NSN 4810-00-529-4316

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-529-4316

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.500 inches
Offset Distance:
0.625 inches
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Open
Connection Style:
Inverted flar (tube) 1st end
Connection Type:
Threaded internal tube 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
16 1st end
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Seat Angle:
60.0 degrees 1st end
Voltage In Volts And Current Type:
18.0 dc and 28.5 dc
Outside Diameter Tube Accommodated:
0.500 inches 1st end
Material:
Aluminum alloy seat
Media For Which Designed:
Hydraulic fluid, mineral base single response
Surface Treatment:
Anodize
Style Designator:
Straight through w/offset
Thread Series Designator:
Unf 1st end
Shelf Life:

N/a

NSN 4810-00-529-4316

Solenoid Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

