NSN 4810-00-529-4316

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-529-4316 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.500 inches Offset Distance: 0.625 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open **Connection Style:** Inverted flar (tube) 1st end **Connection Type:** Threaded internal tube 1st end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 16 1st end **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end Seat Angle: 60.0 degrees 1st end **Voltage In Volts And Current Type:** 18.0 dc and 28.5 dc **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Aluminum alloy seat Media For Which Designed: Hydraulic fluid, mineral base single response **Surface Treatment:** Anodize **Style Designator:** Straight through w/offset **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

NSN 4810-00-529-4316

Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0