

View Online at <https://aerobasegroup.com/nsn/4810-00-534-4682>

Thread Class:

3b

End Connection Quantity:

4

Valve Discharge Flow Rate:

3.5 gallons per minute

End Application:

Aircraft hydraulic system; t.O. 9h8-14-259-3 fig 1

Current Rating In Amps:

0.6

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.563 inches and 0.750 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Flow Pattern Quantity:

3

Spool Position Quantity:

2

Spool Quantity:

1

Special Features:

Manufacturers suggested name valve assembly, solenoid pilot actuated selector; media mil-h-83282 or mil-h-46170; operating pressure 250 to 3000 psig; service medium and ambient temp -65 to +160 degrees feh; return port per ms33649-8, all others ms33649-6; electrical connector per ms3102c10sl4p; pull type solenoid; continuous solenoid duty cycle; over-all size 5.44 x 4.50 x 3.50 inches; wt 1.9 lbs

Thread Series Designator:

Unjf

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A506h0