## NSN 4810-00-541-6054



Gate Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-00-541-6054 Flange Diameter: 12.375 inches **Bonnet Type:** Outside screw-yoke **Bonnet Attachment Method: Bolted Bolt Hole Quantity:** 14 **Current Rating In Amps:** 44.200 and 0.026 **Valve Operation Method:** Electric motor **Connection Type:** Flange, round w/holes Valve Size: 8.000 inches **Maximum Operating Pressure And Media For Which Designed:** 50.0 pounds per square inch water, fresh Stem Type: Nonrising **Voltage In Volts And Current Type:** 115.0 ac **Face To Face Distance:** 11.563 inches Flange Face Design: Plain **Inlet Relationship With Outlet:** Identical Phase: Three **Special Features:** Face to face distance 11.5 min 11.563 maximum in.; flange thickness 0.875 min in.; bolt hole dia. 0.688 nom in.; bolt circle dia. 11.063 nom in.; flow control device: disk; end connection qty: 2; 1 position indicator; flange faces and all interior surfaces to be neoprene coated approx 0.063 in. Thk except nickel copper Frequency In Hertz: 60.0 Material: Steel body Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 4810-00-541-6054

Gate Valve - Page 2 of 2



Fiig:

A500a0