NSN 4810-00-541-6054

Gate Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-541-6054

Flange Diameter:

12.375 inches

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

14

Current Rating In Amps:

44.200 and 0.026

Valve Operation Method:

Electric motor

Connection Type:

Flange, round w/holes

Valve Size:

8.000 inches

Maximum Operating Pressure And Media For Which Designed:

50.0 pounds per square inch water, fresh

Stem Type:

Nonrising

Voltage In Volts And Current Type:

115.0 ac

Face To Face Distance:

11.563 inches

Flange Face Design:

Plain

Inlet Relationship With Outlet:

Identical

Phase:

Three

Special Features:

Face to face distance 11.5 min 11.563 maximum in.; flange thickness 0.875 min in.; bolt hole dia. 0.688 nom in.; bolt circle dia. 11.063 nom in.; flow control device: disk; end connection qty: 2; 1 position indicator; flange faces and all interior surfaces to be neoprene coated approx 0.063 in. Thk except nickel copper

Frequency In Hertz:

60.0

Material:

Steel body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4810-00-541-6054

Gate Valve - Page 2 of 2

Fiig: A500a0

