

View Online at <https://aerobasegroup.com/nsn/4810-00-541-6055>

**Flange Diameter:**

10.125 inches

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

12

**Current Rating In Amps:**

44.200 and 0.026

**Valve Operation Method:**

Electric motor

**Connection Type:**

Flange, round w/holes

**Valve Size:**

6.000 inches

**Maximum Operating Pressure And Media For Which Designed:**

50.0 pounds per square inch water, fresh

**Stem Type:**

Nonrising

**Voltage In Volts And Current Type:**

115.0 ac

**Face To Face Distance:**

10.563 inches

**Flange Face Design:**

Plain

**Inlet Relationship With Outlet:**

Identical

**Phase:**

Three

**Special Features:**

Face to face distance 10.5 min 10.563 maximum in.; flange thickness 0.812 min in.; bolt hole dia. 0.688 nom in.; bolt circle dia. 8.875 nom in.; flow control device: disk; end connection qty: 2; 1 position indicator; flange faces and all interior surfaces to be neoprene coated approx 0.063 in. Thk except nickel copper

**Frequency In Hertz:**

60.0

**Material:**

Steel body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500a0