

View Online at <https://aerobasegroup.com/nsn/4810-00-541-6055>

Flange Diameter:

10.125 inches

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

12

Current Rating In Amps:

44.200 and 0.026

Valve Operation Method:

Electric motor

Connection Type:

Flange, round w/holes

Valve Size:

6.000 inches

Maximum Operating Pressure And Media For Which Designed:

50.0 pounds per square inch water, fresh

Stem Type:

Nonrising

Voltage In Volts And Current Type:

115.0 ac

Face To Face Distance:

10.563 inches

Flange Face Design:

Plain

Inlet Relationship With Outlet:

Identical

Phase:

Three

Special Features:

Face to face distance 10.5 min 10.563 maximum in.; flange thickness 0.812 min in.; bolt hole dia. 0.688 nom in.; bolt circle dia. 8.875 nom in.; flow control device: disk; end connection qty: 2; 1 position indicator; flange faces and all interior surfaces to be neoprene coated approx 0.063 in. Thk except nickel copper

Frequency In Hertz:

60.0

Material:

Steel body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500a0