NSN 4810-00-542-4974

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-542-4974

view Offiline at https://aerobasegroup.com/hish/4010-
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
212.0 degrees fahrenheit single response
Current Rating In Amps:
0.230
Valve Operation Method:
Solenoid
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
0.750 inches
Maximum Operating Pressure:
150.0 pounds per square inch 3rd response
Voltage In Volts And Current Type:
115.0 dc
Outside Diameter:
3.812 inches all ends
Face To Face Distance:
4.500 inches
Thickness:
0.438 inches all ends
Bolt Hole Diameter:
0.562 inches all ends
Bolt Circle Diameter:
2.688 inches all ends
Flange Face Design:
Plain all ends
Material:
Plastic flow control device
Media For Which Designed:

Fuel/oil, hydrocarbon 2nd response

NSN 4810-00-542-4974

Solenoid Valve - Page 2 of 2



Style	Des	siar	ato	r-
Otylo		, gi	iato	

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0