Rotary Electro-mechanical Actuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-554-6623

| Terminal Type: |
|---|
| Connector |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 135.0 degrees fahrenheit |
| Current Type: |
| Dc |
| Operating Speed At Rated Capacity In Rpm: |
| 30.0 |
| Maximum Operating Altitude Rating: |
| 65000.0 feet |
| Shaft Rotation Direction: |
| Clockwise and counterclockwise |
| Drive Type: |
| Direct |
| Duty Cycle: |
| Intermittent |
| Current Rating In Amps: |
| 1.8 |
| Clutch Type: |
| Jaw |
| Rotation In Deg: |
| 90.0 |
| Output Drive Torque Rating: |
| 55.0 foot-pounds |
| Limit Switch Control: |
| Included |
| Manual Override: |
| Included |
| Angular Shaft Rotation: |
| Adjustable |
| Intermittent Operation Duty Cycle: |
| 0.5 seconds on and 3.0 seconds off |
| Mounting Facility: |
| Unthreaded mounting holes |
| Voltage In Volts: |
| 26.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

Yes - demil/mli

NSN 4810-00-554-6623

Rotary Electro-mechanical Actuator - Page 2 of 2

Fiig: A30500

