

View Online at <https://aerobasegroup.com/nsn/4810-00-554-8132>

Thread Class:

3b all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Open

Maximum Operating Temp:

200.0 degrees fahrenheit single response

Connection Style:

Flar (tube) all ends

Current Rating In Amps:

1.200

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal tube all ends

Mounting Position:

Horizontal

Maximum Operating Pressure:

20.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Voltage In Volts And Current Type:

28.0 dc

Outside Diameter Tube Accommodated:

0.500 inches all ends

Material:

Stainless steel flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type1 military specification single treatment response

Style Designator:

Straight thru

Test Data Document:

43999-na5-6420-2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.