

View Online at <https://aerobasegroup.com/nsn/4810-00-554-8132>

**Thread Class:**

3b all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Piston

**Flow Control Device Normal Operation Position:**

Open

**Maximum Operating Temp:**

200.0 degrees fahrenheit single response

**Connection Style:**

Flar (tube) all ends

**Current Rating In Amps:**

1.200

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal tube all ends

**Mounting Position:**

Horizontal

**Maximum Operating Pressure:**

20.0 pounds per square inch single response

**Thread Size:**

0.750 inches all ends

**Voltage In Volts And Current Type:**

28.0 dc

**Outside Diameter Tube Accommodated:**

0.500 inches all ends

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type1 military specification single treatment response

**Style Designator:**

Straight thru

**Test Data Document:**

43999-na5-6420-2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.