## NSN 4810-00-555-1612

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-555-1612

**Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.036 inches Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss 1st end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 16 1st end **Inlet/outlet Operating Pressure Differential:** 50.0 pounds per square inch **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Voltage In Volts And Current Type:** 30.0 dc and 18.0 dc **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Steel seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Straight thru **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

## NSN 4810-00-555-1612

Solenoid Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0