NSN 4810-00-560-8105

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-560-8105

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Offset Distance:
0.500 inches
Flow Control Device:
Poppet
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Flared (tube) all ends
Current Rating In Amps:
0.300
Valve Operation Method:
Solenoid
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 all ends
Maximum Operating Pressure:
6000.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Seat Angle:
37.0 degrees 1st end
Voltage In Volts And Current Type:
115.0 ac
Phase:
Single
Frequency In Hertz:
60.0
Material:
Aluminum seat
Media For Which Designed:
Nitrogen, liquid 2nd response
Surface Treatment:
Anodize

NSN 4810-00-560-8105

Solenoid Valve - Page 2 of 2

Style Designator:

Straight through w/offset

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

