

View Online at <https://aerobasegroup.com/nsn/4810-00-564-7793>

Thread Class:

3b

End Connection Quantity:

4

End Application:

Applicable t.O. 9h8-4-111-3 fig 6; usable on code a

Current Rating In Amps:

0.7

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss

Features Provided:

Base mounted and continuous duty and manual override

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.750 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Flow Pattern Quantity:

4

Spool Position Quantity:

2

Spool Quantity:

1

Special Features:

Manufacturers suggested name valve assembly, 4 way selector; media fluid mil-h-83282 or mil-h-46170; pressure and cylinder ports pressure rating: operating 3000 psig, proof 4500 psig, burst 7500 psig; return port pressure ratings: operating 50 psig, proof 2250 psig, burst 3750 psig; ambient and oil temp range -65 to +160 degrees feh; ports per ms33649-8; mounting hole (4) 0.203 to 0.224 inch diameter; wt 1.87 lbs; major component parts: solenoid assembly 13188, shuttle and sleeve assembly 14303, cured dated items repair kit 6132100 (use until exhausted, then use 32806); valve overhaul repair kit 7132100 (use until exhausted, then use 37169)

Thread Series Designator:

Unjf

Furnished Items And Quantity:

1 knob

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A506h0