

View Online at <https://aerobasegroup.com/nsn/4810-00-566-1454>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Aperture Diameter:

0.047 inches

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Open

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

16 1st end

Inlet/outlet Operating Pressure Differential:

4.0 pounds per square inch

Maximum Operating Pressure:

750.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Voltage In Volts And Current Type:

14.0 dc and 30.0 dc

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Special Features:

Manufacturers suggested name is valve assembly - manifold drip

Material:

Stainless steel seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Passivate

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0