NSN 4810-00-566-1454

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-566-1454 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.047 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open **Connection Style:** Flared (tube) 1st end **Valve Operation Method:** Solenoid **Connection Type:** Threaded external tube 1st end **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 16 1st end **Inlet/outlet Operating Pressure Differential:** 4.0 pounds per square inch **Maximum Operating Pressure:** 750.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Voltage In Volts And Current Type:** 14.0 dc and 30.0 dc **Outside Diameter Tube Accommodated:** 0.500 inches 1st end **Special Features:** Manufacturers suggested name is valve assembly - manifold drip Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:**

Passivate

Thread Series Designator:

Unf 1st end

NSN 4810-00-566-1454

Solenoid Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0