NSN 4810-00-569-6503



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-00-569-6503 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.312 inches Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 200.0 degrees fahrenheit 2nd response **Connection Style:** Plain, optional en (pipe) all ends **Current Rating In Amps:** 0.095 and 0.087 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Vertical **Inlet/outlet Operating Pressure Differential:** Between 400.0 pounds per square inch and 750.0 pounds per square inch **Maximum Operating Pressure:** 750.0 pounds per square inch 2nd response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 110.0 ac and 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Plastic polytetrafluoroethylene seat Media For Which Designed: Alcohol, ethyl 1st response **Style Designator:** Straight thru **Thread Series Designator:**

N/a

Npt all ends

Shelf Life:

NSN 4810-00-569-6503 Solenoid Valve - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A046b0