## NSN 4810-00-569-6503

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-569-6503

#### Thread Direction:

Right-hand all ends

#### Aperture Diameter:

0.312 inches

## Flow Control Device:

Disk

#### Flow Control Device Normal Operation Position:

Closed

#### Maximum Operating Temp:

200.0 degrees fahrenheit 2nd response

#### **Connection Style:**

Plain, optional en (pipe) all ends

#### **Current Rating In Amps:**

0.095 and 0.087

#### Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal pipe all ends

#### Mounting Position:

Vertical

## Inlet/outlet Operating Pressure Differential:

Between 400.0 pounds per square inch and 750.0 pounds per square inch

## Maximum Operating Pressure:

750.0 pounds per square inch 2nd response

Thread Size:

0.250 inches all ends

### Voltage In Volts And Current Type:

110.0 ac and 120.0 ac

Phase:

Single

## Frequency In Hertz:

60.0

## Material:

Plastic polytetrafluoroethylene seat

## Media For Which Designed:

Alcohol, ethyl 1st response

## Style Designator:

Straight thru

## Thread Series Designator:

Npt all ends

## Shelf Life:

N/a

# NSN 4810-00-569-6503

Solenoid Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

